

Implementing
“Practical leakage-resilient
symmetric cryptography”

Daniel J. Bernstein

University of Illinois at Chicago,
Technische Universiteit Eindhoven

CHES 2012 paper

“Practical leakage-resilient
symmetric cryptography”

(Faust, Pietrzak, Schipper)

explains how to

“protect against *realistic*
side-channel attacks.”

CHES 2012 paper

“Practical leakage-resilient
symmetric cryptography”
(Faust, Pietrzak, Schipper)

explains how to

“protect against *realistic*
side-channel attacks.”

Sounds great!

But is it secure?

CHES 2012 paper

“Practical leakage-resilient
symmetric cryptography”
(Faust, Pietrzak, Schipper)

explains how to

“protect against *realistic*
side-channel attacks.”

Sounds great!

But is it secure?

Will an implementor
doing what this paper says
actually end up with a
side-channel-protected cipher?

The TCC view:

“What do you mean?

It’s *provably* secure!

We have proofs and theorems!”

The TCC view:

“What do you mean?

It’s *provably* secure!

We have proofs and theorems!”

Macbeth’s view:

“It is a tale

told by an idiot,

full of sound and fury,

signifying nothing.”

The TCC view:

“What do you mean?

It’s *provably* secure!

We have proofs and theorems!”

Macbeth’s view:

“It is a tale

told by an idiot,

full of sound and fury,

signifying nothing.”

My view: Carefully evaluating

side-channel security

requires an implementation.

⇒ Let’s implement the cipher.

Prerequisite: “ F ”,
a “PRF” (or a “weak PRF”)
mapping a k -bit key
and an ℓ -bit nonce
to a $2k$ -bit output.

Prerequisite: “ F ”,
a “PRF” (or a “weak PRF”)
mapping a k -bit key
and an ℓ -bit nonce
to a $2k$ -bit output.

Hmmm, this is vague.

What’s k ? ℓ ? F ?

Practical cryptography
requires complete specification.

Prerequisite: “ F ”,
a “PRF” (or a “weak PRF”)
mapping a k -bit key
and an ℓ -bit nonce
to a $2k$ -bit output.

Hmmm, this is vague.

What’s k ? ℓ ? F ?

Practical cryptography
requires complete specification.

My best guesses:

$k = 128$; $\ell = 127$;

$F_K(p) = \text{AES}_K(0p) \text{AES}_K(1p)$.

First-level cipher Γ :

Input: 128-bit key K ;

standard random 32639-bit string

$p = (p_0, p_1, \dots, p_{255}, p_{256})$;

256-bit nonce

$n = (n_0, n_1, \dots, n_{255})$.

First-level cipher Γ :

Input: 128-bit key K ;

standard random 32639-bit string

$p = (p_0, p_1, \dots, p_{255}, p_{256})$;

256-bit nonce

$n = (n_0, n_1, \dots, n_{255})$.

Compute

$X_0 = K$,

$X_1 = \text{AES}_{X_0}(n_0 p_0)$,

$X_2 = \text{AES}_{X_1}(n_1 p_1), \dots,$

$X_{256} = \text{AES}_{X_{255}}(n_{255} p_{255})$.

First-level cipher Γ :

Input: 128-bit key K ;

standard random 32639-bit string

$p = (p_0, p_1, \dots, p_{255}, p_{256})$;

256-bit nonce

$n = (n_0, n_1, \dots, n_{255})$.

Compute

$X_0 = K$,

$X_1 = \text{AES}_{X_0}(n_0 p_0)$,

$X_2 = \text{AES}_{X_1}(n_1 p_1), \dots,$

$X_{256} = \text{AES}_{X_{255}}(n_{255} p_{255})$.

Output: 256-bit string

$\text{AES}_{X_{256}}(p_{256} 0) \text{AES}_{X_{256}}(p_{256} 1)$.

The final cipher:

Input:

384-bit key K_0, K_1, K_2 ;

512-bit plaintext (a_0, b_0) .

The final cipher:

Input:

384-bit key K_0, K_1, K_2 ;

512-bit plaintext (a_0, b_0) .

Compute

$$(a_1, b_1) = (a_0, b_0 \oplus \Gamma_{K_0}(a_0));$$

$$(a_2, b_2) = (a_1 \oplus \Gamma_{K_1}(b_1), b_1);$$

$$(a_3, b_3) = (a_2, b_2 \oplus \Gamma_{K_2}(a_2)).$$

The final cipher:

Input:

384-bit key K_0, K_1, K_2 ;

512-bit plaintext (a_0, b_0) .

Compute

$$(a_1, b_1) = (a_0, b_0 \oplus \Gamma_{K_0}(a_0));$$

$$(a_2, b_2) = (a_1 \oplus \Gamma_{K_1}(b_1), b_1);$$

$$(a_3, b_3) = (a_2, b_2 \oplus \Gamma_{K_2}(a_2)).$$

Output:

512-bit ciphertext (a_3, b_3) .

I implemented this cipher
during a talk this morning.

I implemented this cipher
during a talk this morning.

“Code simplicity?”

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

“Validation status?”

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

“Validation status?” Bad.

Surely there are bugs.

Practical cryptography requires test vectors.

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

“Validation status?” Bad.

Surely there are bugs.

Practical cryptography requires test vectors.

“Source of random p ?”

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

“Validation status?” Bad.

Surely there are bugs.

Practical cryptography requires test vectors.

“Source of random p ?” Bad.

I used C’s `random()`.

I implemented this cipher during a talk this morning.

“Code simplicity?” Not bad, assuming AES is provided.

I used AES from OpenSSL.

“Validation status?” Bad.

Surely there are bugs.

Practical cryptography requires test vectors.

“Source of random p ?” Bad.

I used C’s `random()`.

I’m going to hell.

“Code availability?”

“Code availability?” Good.

cr.yp.to/aesgonewild.html

“Code availability?” Good.

cr.yp.to/aesgonewild.html

“Speed?”

“Code availability?” Good.

cr.yp.to/aesgonewild.html

“Speed?” Horrifying.

Encrypting 64 bytes:

close to 1 million cycles

on one core of my laptop.

“Code availability?” Good.

cr.yp.to/aesgonewild.html

“Speed?” Horrifying.

Encrypting 64 bytes:

close to 1 million cycles

on one core of my laptop.

But *faster than FHE*.

“Code availability?” Good.

cr.yp.to/aesgonewild.html

“Speed?” Horrifying.

Encrypting 64 bytes:

close to 1 million cycles

on one core of my laptop.

But *faster than FHE*.

“Security?” Unclear!

Try hyperthreading, DPA, etc.

Maybe chosen- n templates

will discover secret n ?

Don't let slow ciphers

evade security evaluation.